

Simplifying a Complex Roof Form

Innovation Lowers Building Height and Reduces Costs

By David A. Platten, P.E. and Lee W. Slade, P.E.

American Airlines Center in Dallas, Texas, is a multi-purpose arena that seats 19,200 for NBA basketball, 18,500 for NHL hockey and 20,000 for center-staged events. The roof structure is an innovative and surprisingly economical response to the classic but complex cross-vault architectural roof shape.




Walter P. Moore added an external post-tensioned concrete tension tie embedded in the upper concourse floor framing to economically provide the lateral resistance usually provided by buttresses in traditional barrel vault construction. This unique mix of structural steel and post-tensioned concrete results in a design that takes maximum advantage of the structural depth created by the arch shapes of the cross-vault form. Though internally tied structural systems have been utilized on many recently completed NBA/NHL arenas, these systems have commonly required significant increases in the building height to provide unobstructed fan sightlines below the cross ties. By using the external tension tie, the building was effectively shortened by 15 feet, resulting in structural frame cost savings of an estimated \$2 million and additional savings in building façade and MEP systems. The design also provided a long-span roof steel erection method that was simple and safe.

"...unique mix of structural steel and post-tensioned concrete..."

An innovative show rigging support system is integrated into the roof-truss design to improve economy, safety, aesthetics, and to streamline building operations. By establishing a truss spacing of approximately 11 feet and designing the truss bottom chords to resist rigging loads along their length, the engineers eliminated the need for a separate rigging grid. In addition to saving steel tonnage, this integrated solution provides riggers with safe and easy access from the catwalk system, which in turn enables the Center to attract and quickly prepare for a variety of show events.

Collaboration between the architects and engineers resulted in simplification of the building geometry without compromising the desired roof form. In the original architectural design, the cross-vault intersection occurred at a common elevation at the center of the building. At the structural engineer's suggestion, this geometry was greatly simplified by the architect without compromising the desired roof form. To standardize truss shapes and simplify truss connections, cross-vault intersections were established at 45 degrees with matching vault radii in the corners of the building. This created framing in the corners that was symmetric about the valleys, as well as identical in all four corners, greatly improving economy and construction simplicity. The long-side vault radius was flattened between the corners, and its apex was raised slightly



REGISTER NOW TO ATTEND THIS FULL-DAY SEMINAR ON SPECIFYING AND DESIGNING WITH STEEL JOISTS.

"HOW TO MAKE STEEL JOIST CONSTRUCTION WORK HARDER FOR YOU."

This in-depth 6-part program sponsored by the SJI & NCSEA goes into great detail to help you determine when steel joist construction is the best solution. It includes information which will help engineers, architects and design professionals with steel joist design and construction. Presenters are steel joist engineering professionals and employees of SJI member companies.

Your \$295 seminar fee includes SJI Specs and Load Tables, a comprehensive instructional binder (combined total value of \$75), continental breakfast, and lunch.

Each participant earns .75 CEUs or 7.5 PDHs.

Get details and register at www.steeljoist.org.

2004 SCHEDULE

March 23	Long Beach, CA
April 20	Kansas City, MO
May 25	Providence, RI
July 13	Oak Brook, IL
Sept 14	Sacramento, CA
Nov 16	Atlanta, GA

Steel Joist Institute
(843) 626-1995
Steeljoist.org





relative to the short-side vault, resulting in the definition of a central framing rectangle 110 feet by 210 feet. The primary load-carrying structure, then, is a “table-top” system where four primary trusses occur at the perimeter of the central rectangle, or “table,” with four “leg” trusses extending from the corners of the rectangle, at the valleys, to the tension tie elevation at the upper concourse level.

“...cross-vault intersections were established at 45 degrees...”

Use of the externally tied roof framing system allowed a clear span area of 330 feet by 430 feet to be framed with trusses having depths of only 13 feet. This shallow depth allowed for shop-welded fabrication of the trusses and shipping of complete truss sections in lengths of up to 60 feet, saving both time and money. ■

Use of the externally tied roof framing system allowed a clear span area of 330 feet by 430 feet



Preparation Material for FE/PE Exams

NCEES offers hard copy and electronic exam preparation material to civil and structural candidates. Sample questions were developed by the same groups that created the exams, and they conform to current exam specifications. Solutions are provided. Structural I PE and Civil PE candidates can now take a timed Internet Practice Exam at the NCEES web site. For more information visit the NCEES web site at www.ncees.org or call 1-800-250-3196.

National Council of Examiners for Engineering and Surveying
www.ncees.org 1-800-250-3196

*David A. Platten, P.E., is Managing Director of Walter P. Moore's Dallas office. DPlatten@WalterPMoore.com Lee W. Slade, P.E., is Executive Director of Walter P. Moore's Structural Engineering Group. LSlade@WalterPMoore.com
 Photos courtesy of Hillwood and Walter P. Moore.*

For Advertiser Information, visit www.structuremag.org